

Entry Line

The budget-friendly alternative

With a Full HD screen, the Entry Line offers all the basic features you need. It's a budget-friendly alternative to the Pro Line.



Specifications

Screen	55"	65"	70"
Bezel color	Sand blasted aluminium (black)	Sand blasted aluminium (black)	Sand blasted aluminium (black)
Diagonal	55 inch	65 inch	70 inch
Panel type	Full HD LED	Full HD LED	Full HD LED
Maximum Resolution	1920 x 1080 @ 60Hz	1920 x 1080 @ 60Hz	1920 x 1080 @ 60Hz
Response Time Panel	6 ms	6 ms	6 ms
Glass Plate	Anti-Glare	Anti-Glare	Anti-Glare
Glass Thickness	4 mm / 0.16 inches	4 mm / 0.16 inches	4 mm / 0.16 inches
Glass Hardness	Mhos 7	Mhos 7	Mhos 7
Aspect ratio	16:9	16:9	16:9
Contrast ratio	1400:1	1400:1	4000:1
Brightness	350 cd/m2	350 cd/m2	300 cd/m2
Number of colours	8 bit (16.7M)	8 bit (16.7M)	8 bit (16.7M)
Viewing Angle	178°	178°	178°
Panel Refresh Rate	120Hz	120Hz	120Hz

Modules	55"	65"	70"
PC module slot	Yes	Yes	Yes
DVD / Blu-ray module	N/A	N/A	N/A

Touch module	55"	65"	70"
Touch module	Entry Line 55" HD	Entry Line 65" HD	Entry Line 70" HD
Type	IR-pro	IR-pro	IR-pro
Multi-touch	Yes (10 points)	Yes (10 points)	Yes (10 points)
Multi writing	Yes (5 points)	Yes (5 points)	Yes (5 points)
Auto-calibration	Yes	Yes	Yes
Resistant to sunlight	Yes	Yes	Yes
Supported OS	Windows 7, 8.1 & 10/Mac OS/ Linux/Android and Chrome OS	Windows 7, 8.1 & 10/Mac OS/ Linux/Android and Chrome OS	Windows 7, 8.1 & 10/Mac OS/ Linux/Android and Chrome OS

Audio	55"	65"	70"
Speakers	Stereo (2 speakers)	Stereo (2 speakers)	Stereo (2 speakers)
Power	2 x 10 Watt / 8Ω	2 x 10 Watt / 8Ω	2 x 10 Watt / 8Ω
Microphone	N/A	N/A	N/A

Special features	55"	65"	70"
ProMenu	Yes, version 2.0	Yes, version 2.0	Yes, version 2.0
NFC reader/writer	N/A	N/A	N/A
Pen-tray	N/A	N/A	N/A
Over the Air Updates (OTA)	Yes	Yes	Yes

Connections	55"	65"	70"
HDMI 1.4	3 (3x 1.4)	3 (3x 1.4)	3 (3x 1.4)
HDMI 2.0	N/A	N/A	N/A
HDMI Port with MHL	Yes, HDMI 3	Yes, HDMI 3	Yes, HDMI 3
VGA + Audio in	3	3	3
VGA Passthrough	1	1	1
Audio output analog	3,5 mm Stereo Jack (adjustable)	3,5 mm Stereo Jack (adjustable)	3,5 mm Stereo Jack (adjustable)
Audio output digital	Coaxial (fixed)	Coaxial (fixed)	Coaxial (fixed)
RS232 control	1 (Sub-D, 9 pins)	1 (Sub-D, 9 pins)	1 (Sub-D, 9 pins)
AV	1 (including adapter to 3 x RCA connector)	1 (including adapter to 3 x RCA connector)	1 (including adapter to 3 x RCA connector)
USB Touch port	1 (USB-B female)	1 (USB-B female)	1 (USB-B female)
LAN port for online updates	1 (RJ-45)	1 (RJ-45)	1 (RJ-45)
Wi-Fi for online updates	Yes	Yes	Yes
Webcam Mount + top USB	N/A	N/A	N/A

Environmental conditions	55"	65"	70"
Operation Temperature	0 - 38°C / 32 - 100.4 °F	0 - 38°C / 32 - 100.4 °F	0 - 38°C / 32 - 100.4 °F
Storage Temperature	-20 - 60°C / -4 - 140 °F	-20 - 60°C / -4 - 140 °F	-20 - 60°C / -4 - 140 °F
Storage Humidity	10% - 90%	10% - 90%	10% - 90%
Operation Humidity	10% - 90%	10% - 90%	10% - 90%
Altitude	< 2000 meter / < 6561.68 feet	< 2000 meter / < 6561.68 feet	< 2000 meter / < 6561.68 feet

General Information	55"	65"	70"
Voltage	~ 100-240 V (50/60Hz)	~ 100-240 V (50/60Hz)	~ 100-240 V (50/60Hz)
Power consumption (Without modules)	156 watt	200 watt	208 watt
Stand-by power consumption	≤ 0,5 Watt	≤ 0,5 watt	≤ 0,5 watt
Gross Weight	45 kg / 99.21 lbs	61 kg / 134.48 lbs	72 kg / 158.73 lbs
Netto Weight	35 kg / 77.16 lbs	45 kg / 99.21 lbs	56 kg / 123.46 lbs
Dimensions of the screen (W x H x D)	1302 x 819 x 96 mm / 51.26 x 32.24 x 3.8 inches	1521 x 943 x 97 mm / 59.88 x 37.13 x 3.82 inches	1664 x 1034 x 97 mm / 65.51 x 40.71 x 3.82 inches
Dimensions of the total packing (W x H x D)	1458 x 932 x 220 mm / 57.4 x 36.69 x 8.66 inches	1695 x 1090 x 235 mm / 66.73 x 42.91 x 9.25 inches	1803 x 1160 x 243 mm / 70.98 x 45.67 x 9.57 inches
VESA Standard	VESA 400 x 400	VESA 600 x 400	VESA 600 x 400
Certifications	CE/FCC/IC and RCM	CE/FCC/IC and RCM	CE/FCC/IC and RCM
Warranty	5 year	5 year	5 year